

PAT400 series

Portable appliance testers



- **10,000 memory storage with USB download**
- **Large 5.7" ¼ VGA backlit full colour screen for clear results**
- **200 mA; 10 A and 25 A Bond Test with high duty cycle for repetitive testing (PAT410 – 200 mA only)**
- **Selectable PASS/FAIL limits provide instant indication of a faulty asset**
- **Optional barcode scanner and printer available to save time typing asset IDs**
- **230 V and 110 V operation for industrial, commercial and residential applications**

DESCRIPTION

The PAT400 series from Megger is a new generation of downloading portable appliance testers, fully testing portable electrical equipment to the latest edition of the Code of Practice for the In-Service Inspection and Testing of Electrical Equipment. There are 3 products in the range; the PAT410 providing a low-profile 230 V only solution without the added weight required of 110 V operation, plus a database capacity for up to 10,000 test results. The PAT420 provides the same extensive memory and downloading capability, and has the added features of 110 V operation, and also 10 A and 25 A earth bond testing. The PAT450, the top of the range, has all of these features and includes 1.5 kV and 3 kV flash testing, ideal for tool hire outlets and service workshops where flash testing is routine. All products in the range have a high duty-cycle, with the design tailored to fast testing, easy operation, and all-day use. The PAT400s feature a unique fast-re-start, so that when moving the tester from one room to another, it re-starts instantly from the same menu where it was unplugged. This is a significant timesaver, so allowing more tests per day.

USB communication provides convenient download to a standard USB memory stick., and an on-board 10,000 record memory provides interruption-free testing for improved efficiency, with a large QWERTY keypad for fast data entry. Data is directly compatible with Megger PowerSuite® software for professional certification, and all products have the option of a barcode scanner and a thermal transfer barcode label printer operating directly from the USB port. Thermal transfer labels are highly resistant, stable and easily available. The PAT420 and PAT450 have dual 230 V and 110 V operation for complete industrial, commercial and residential applications.

5 soft-keys give direct access to frequently used functions, accelerating navigation through menus and therefore increasing productivity, where time is money. Both standard

and customer configurable test groups are available for fast, flexible asset testing.

Tests available in the range include 250 V and 500 V insulation tests, 200 mA, 10 A and 25 A earth bond tests, differential, touch and alternative (substitute) leakage tests, operational VA tests, RCD trip-tests for portable RCDs, anti-surge and RCD protected extension leads and power cords. RCD testing is now a requirement of the UK Code of Practice.

Accessories supplied with all models include a combined earth-bond and insulation test lead, an adaptor for testing 230 V extension leads, a laptop power supply adaptor, and a carry-case for convenient product and lead storage. All instruments also include Download Manager software, to enable data to be converted into a CSV format which can be read directly on a PC using Microsoft® Excel.

Megger PowerSuite software can be purchased to compliment any PAT400, providing full databased asset management and professional electronic certificate generation, providing options for multiple clients and locations.

APPLICATIONS

There is a legal requirement for any landlord, employer or owner of a place of work or public place, to ensure that all electrical equipment accessible by tenants, employees or the public is maintained in a safe condition, and an acceptable method of ensuring this is by routine electrical testing. This can be performed by electrical contractors, specialist PAT testing organisations, maintenance departments, or facilities management companies.

The PAT400 range is suitable for performing portable appliance testing in locations such as hotels, public houses, schools, colleges, nurseries, shops, offices, theatres, banks, restaurants, cafés, sports and leisure facilities, cinemas, factories and hair salons etc. where high volume testing

requires that accurate records may be difficult to maintain, or aided by, on-board memory and download to management software. The PAT450 is particularly suitable for use in tool-hire shops where equipment is routinely tested prior to hire, or service workshops where deep disassembly is routine, and will perform a flash test in addition to standard PAT tests.

| | PAT410 | PAT420 | PAT450 |
|----------------------------------|--------|--------|--------|
| SUPPLY | | | |
| 230 V | ■ | ■ | ■ |
| 110 V | | ■ | ■ |
| Supply measurement | ■ | ■ | ■ |
| EARTH BOND/CONTINUITY | | | |
| 200 mA | ■ | ■ | ■ |
| 10 A | | ■ | ■ |
| 25 A | | ■ | ■ |
| Bond lead null | ■ | ■ | ■ |
| INSULATION TEST | | | |
| 250 V | ■ | ■ | ■ |
| 500 V | ■ | ■ | ■ |
| ALTERNATIVE LEAKAGE TESTS | | | |
| Substitute | ■ | ■ | ■ |
| Differential | ■ | ■ | ■ |
| Touch current | ■ | ■ | ■ |
| OPERATION TEST | | | |
| VA Measurement | ■ | ■ | ■ |
| EXTENSION LEAD TESTS | | | |
| Earth bond | ■ | ■ | ■ |
| Insulation | ■ | ■ | ■ |
| Polarity | ■ | ■ | ■ |
| Portable RCD tests | ■ | ■ | ■ |
| FLASH TEST | | | |
| 1.5 kV and 3 kV | | | ■ |
| OTHER FEATURES | | | |
| Low-profile light weight | ■ | | |
| Auto test routine | ■ | ■ | ■ |
| Manual testing | ■ | ■ | ■ |
| Fuse check | ■ | ■ | ■ |
| Colour display | ■ | ■ | ■ |
| 110 V test connection | | ■ | ■ |
| Configurable tests times | ■ | ■ | ■ |
| Selectable pass limits | ■ | ■ | ■ |
| Lead storage pouch | ■ | ■ | ■ |
| 10,000 record on-board storage | ■ | ■ | ■ |
| Download to USB memory stick | ■ | ■ | ■ |
| PowerSuite compatible | ■ | ■ | ■ |

SPECIFICATIONS

Electrical supply range

| | |
|----------------|---|
| PAT410 | 230 V \pm 10% @ 50/60 Hz |
| PAT420, PAT450 | 110 V \pm 10% + 110 V \pm 10% @ 50/60 HZ |

Bond test (10 A and 25 A) (not PAT410)

| | |
|-----------------------------------|--|
| Open circuit voltage: | 9V a.c. \pm 10% \pm 0.1 V (Supply: 230 V 50Hz) |
| Earth bond resistance accuracy: | \pm 5% \pm 3 digits (0 to 0.49 Ω) \pm 5% \pm 5 digits 0.5 to .99 Ω) |
| Earth bond resistance resolution: | 10 m Ω (0 to 1.99 Ω) |
| Display range: | 0 to 1.99 Ω |

Continuity test (200 mA)

| | |
|-----------------------------------|--|
| Continuity test voltage: | 4.0 V d.c. -0% +10% |
| Continuity resistance accuracy: | \pm 5% \pm 3 digits (0 to 0.49 Ω) \pm 5% \pm 5 digits 0.5 to .99 Ω) |
| Continuity resistance resolution: | 10 m Ω (1 to 19.99 Ω) |
| Display range: | 0 to 19.99 Ω |

Insulation test (250 V and 500 V)

| | |
|---|--|
| Insulation resistance accuracy (230 V): | \pm 2% \pm 5 digits (0 to 19.99 M Ω) \pm 5% \pm 10 digits (20 to 99.99 M Ω) |
| Insulation resistance resolution: | 0.01 M Ω |
| Display range: | 0 to 99.99 M Ω |

Substitute leakage test

| | |
|-----------------------------|---|
| Test voltage and frequency: | 40 V a.c. \pm 10% nominal mains frequency |
| Leakage current accuracy: | \pm 5% \pm 5 digits |
| Leakage current resolution: | 0.01 mA |
| Display range: | 0 to 19.99 mA |

Differential leakage current

| | |
|--|-------------------------|
| Test voltage and frequency: | Nominal mains supply |
| Differential leakage current accuracy: | \pm 5% \pm 5 digits |
| Differential leakage current resolution: | 0.01 mA |
| Display range: | 0 to 19.99 mA |

Touch current test

| | |
|-----------------------------|-------------------------|
| Test voltage and frequency: | Nominal mains supply |
| Touch current accuracy: | \pm 5% \pm 5 digits |
| Touch current resolution: | 0.01 mA |
| Display: | 0 to 10 mA |

Operational test

| | |
|-----------------------------|---|
| Test voltage and frequency: | Nominal mains supply |
| VA rating: | 230 V 3700 VA 110 V 1800 VA |
| VA accuracy: | \pm 5% \pm 10 digits (0 - 99 VA) \pm 5% \pm 50 digits (100 VA - 999 VA) \pm 5% \pm 100 digits (1000 VA - 3700 VA) |
| Resolution: | 1 VA (0 to 3700 VA) |
| Display range: | 0 to 3990 VA |

Extension lead test

| | |
|------------------------|--|
| Tests performed: | Bond, insulation and polarity |
| Polarity test voltage: | 12 V |
| Polarity checks: | Lead OK Live neutral S/C Live neutral reversed Live/neutral O/C |

Flash test

| | |
|--|--|
| Flash test voltage: | 1500 V a.c. nominal for Class 1 3000 V a.c. nominal for Class 2 |
| Flash test current: | <3.5 mA short circuit @ 253 V primary supply voltage |
| Flash test breakdown current accuracy: | ±5% ±5 digits |
| Flash test breakdown current resolution: | 0.01 mA |
| Display range: | 0 to 3.0 mA |

Portable RCD test

| | |
|-----------------------------|---|
| Test voltage and frequency: | Nominal mains supply |
| Test current accuracy: | -8% to -2% (1/2 x I) +2% to +8% (1 x I, 5 x I) |
| Trip time accuracy: | ±1% ±5 digits |
| Trip time resolution: | 0.1 ms |
| Display range: | 0 to 1999 ms (1/2 x I) 0 to 300 ms (1 x I) 0 to 40 ms (5 x I) |

Fuse test

| | |
|---------------|----------------------------|
| Test voltage: | 3.3 V |
| Warning: | Audible beep if fuse is OK |

Environmental

| | |
|------------------------|--|
| Operating temperature: | -10 to +50 °C |
| Storage temperature: | -20 to +60 °C |
| Humidity: | 90% RH @ -10 to +30 °C 75% RH @ +30 to +50 °C |
| Maximum altitude: | 2000 m |
| Ingress protection: | IP40 |

Weight

| | |
|-------------------------|-----------------|
| PAT410 (with packaging) | 2.7 kg (3.2 kg) |
| PAT420 (with packaging) | 4.4 kg (4.9 kg) |
| PAT450 (with packaging) | 5.0 kg (5.5 kg) |

Dimensions

| | |
|-----------------|-----------------------------|
| PAT410 | 145 (H) x 255 (W) x 320 (L) |
| PAT420 & PAT450 | 180 (H) x 255 (W) x 320 (L) |
| Packaging: | 210 (H) x 280 (W) x 390 (L) |

Safety

IEC 61010-1: CAT II 300 V

EMC

IEC 61326-1: 2006
IEC 61326-2-2: 2005

ORDERING INFORMATION

| Product | Order Code | Product | Order Code |
|--|------------|--|------------|
| PAT410-UK | 1000-745 | Optional accessories | |
| PAT420-UK | 1000-752 | Extension lead adaptor (ELA) 110 V* (BS4343) | 6220-639 |
| PAT450-UK | 1000-755 | 110 V Mains lead adaptor BS1363 - BS4343 | 1000-766 |
| Included accessories | | 415 V Adaptor lead (4 pin) to BS (BS1363) 16 A | 1000-767 |
| Printed quick start guide | | 415 V Adaptor lead (5 pin) to BS (BS1363) 16 A | 1000-770 |
| Full user guide on CD | | Bar code scanner (USB) | 1001-047 |
| Calibration Certificate | | Pass/fail barcode label printer (USB) | 1001-046 |
| Continuity / earth bond lead + probe (black) | 2000-870 | USB lead – PAT – printer | 25970-041 |
| Extension lead adaptor 13 A | 2000-881 | Barcode printer label refills (cartridge) | 90001-010 |
| Flash lead 3.0 KV 3.5 mA (red) (PAT450 only) | 5310-401 | Appliance bar-code labels (1-1000) | 6121-483 |
| Carry case with lead/document pouch | 2000-962 | Roll of 1000 FAIL test labels | 1001-227 |
| Plug adaptor IEC C6 - C13 (3 way 5 A PSU) | 2000-551 | Roll of 1000 PASS test labels | 1000-971 |
| | | PAT accessory pouch | 2001-044 |
| | | PAT test certificate book | 1001-299 |